



TECHNICAL DATA	
STANDARD MATERIALS OF CONSTRUCTION 316 STAINLESS STEEL FLANGED VENTURI FIRE PUMP TEST METERS	
VENTURI:	316L "MACHINED" STAINLESS STEEL CASTING
FLANGES:	316/316L 150-LB WELD-NECK, RAISED FACE, STANDARD BORE FLANGES
WELDING:	ASME PRESSURE VESSEL IX
METER:	4.5" DIAL, (BUNA-N) SEALS, 316 SS BODY, CASE AND WETTED PARTS
VALVES:	316 SS 600 WOG BALL VALVES
FITTINGS:	
ON VENTURI	316SS 1/4" FITTING & VALVES ON VENTURI
&	
ON METER	316 SS 1/4" FITTINGS & VALVES ON METER
HOSES:	(2) 1/4" SS BRAIDED HOSES WITH TEFLON ID

316 STAINLESS STEEL
0-12,000 USGPM / 45,420 LPM

CERTIFIED BY CHARLES P. SUTTON - PRESIDENT

GLOBAL VISION INC.

8800 JEFFERSON HWY
OSSEO, MINNESOTA 55369
763 - 391 - 0990

**FIRE PUMP ASSEMBLY
10" - 744 FLANGED 150#**

DATE:	09/13/08
SCALE:	NTS
DWG #	GVIFP-10-150-FL-SS
	FLANGED